


	PRODUCT CHARACTERISTICS			
	Standard	Requirement	Unit	Results
	PRODUCT DESCRIPTION			
Surface treatment	-	-	-	PUR
Surface complex	-	-	-	Filled PVC wearlayer
Foam	-	-	-	Open Cell Foam
Thickness	EN ISO 24346	-	mm	4.5
Weight	EN ISO 23997	-	kg/m <sup>2</sup>	2.6
Length	EN ISO 24341	-	lm	18
Width	EN ISO 24341	-	lm	2
	TECHNICAL CHARACTERISTICS			
Vertical deformation	EN 14809	≤ 5	mm	≤ 5
Sliding coefficient	EN 13036-4	80 to 110	-	80 to 110
Abrasion resistance	EN ISO 5470-1	≤ 1000	mg	≤ 1000
Indentation resistance	EN 1516	≤ 0.5	mm	≤ 0.5
	CLASSIFICATION			
Fire	EN 13501-1	-	-	Bfl-S1
Anti-bacterial activity (E. coli - S. aureus - MRSA)*	ISO 22196	-	-	> 99 % inhibits growth
	DECLARATION OF PERFORMANCE			
		-	-	Fire Sliding Coefficient Abrasion Resistance

\* The implementation of an effective cleaning method is the best defence against infection