

DESCRIPTION

| | | | |
|------------------------|--------|------------------|-----------|
| Total thickness | EN 428 | mm | 6.00 |
| Thickness of wearlayer | EN 429 | mm | 2 |
| Weight | EN 430 | g/m ² | 9080 |
| Tile size | EN 427 | mm | 635 x 635 |






CLASSIFICATION

| | | | |
|---|-------------|-------|---------------------|
| Norm / Product specification | - | - | EN 649 |
| European classification | EN 685 | class | 34 - 43 |
| K rating | - | class | K5 |
| Fire rating | EN 13 501-1 | class | B _{fl} -s1 |
| Static electrical propensity | EN 1815 | kV | <2 |
| Slip resistance wet: ramp test with oil | DIN 51130 | class | R10 |

PERFORMANCE

| | | | |
|------------------------------|-----------------|-----------------|-------|
| Wear resistance | EN 660.2 | mm ³ | ≤ 2.0 |
| Wear group | EN 649 | - | T |
| Dimensional stability | EN 434 | % | ≤0.25 |
| Shore hardness | EN ISO 868 | H _D | 94 |
| Thermal conductivity | EN 12524 | W/(m.K) | 0.25 |
| Colour fastness | EN 20 105 - B02 | degree | ≥6 |
| Chemical products resistance | EN 423 | - | OK |
| Surface treatment | - | - | PUR |

CE MARKING

| | | | |
|--|----------|---|---|
|  | EN 14041 | - |    |
| | | - |  |